

Flue and Ambient CO Analysis

BACKED BY

UEi
SERVICE+

10
YEAR
WARRANTY



Functions

- Test boilers, cookers, grills, and ovens for CO
- Perform 2-minute appliance sweep test
- Use **KANE LINK™** to connect up to 4 CO Loggers to combine ambient air tests (See COL option on back)
- Save & send results to **KANE LIVE™** app or optional printer
- Measure: CO and Flue Temperature
- Calculate:

Features

- Backed by UEi Service+
- Up to 10-Year warranty with annual recertification
- Large 6-line backlit display
- Temperature w/ K-Type probe inputs
- Protective water trap
- Print to optional printer
- Protective rubber boot with magnet
- DMM-style rotary dial

Includes

- Probe (CP2)
- Rechargeable batteries 3 (AA)
- USB Charging cable (AAC5)
- Quick Start Guide (201996)
- Certificate of calibration



KANE
LINK™

KANE
KANE LIVE

DESIGNED BY
MADE BY
BACKED BY
UEi

We're Proud Supporters of
National Carbon Monoxide
Awareness Association
WWW.NCOAA.US

Specifications

Temperature Measurement

Parameter	Range	Resolution	Accuracy
Flue Temperature	32° to 1112°F (0° to 600°C)	0.1°F (0.1°C)	±(0.3% rdg +3.6°F (2°C))
Inlet Temperature (Internal Sensor)	32° to 122°F (0° to 50°C)	0.1°F (0.1°C)	±2°F (1°C)
Inlet Temperature (External Sensor)	32° to 1112°F (0° to 600°C)	0.2° (0.1°C)	±1.0°F (0.5°C)

Flue Gas Measurement

Parameter	Range	Resolution	Accuracy
Carbon Dioxide	0 to 20%	0.1%	±0.3% volume

Battery Life	>8 hours (continuous with pump on)
Operating Conditions	
Temperature	32° to 113°F (0° to 45°C)
Humidity	15% to 90% R.H.
Storage Temperature	0° to 113°F (-18° to 50°C)
Power Supply	Rechargeable Batteries, USB Charging
Dimensions	
Dimensions	8.54" x 4.18" x 1.86"
Weight	1 lb., 5.1 oz.



Made in UNITED
KINGDOM

